Stock # : R20084-1 SPEC 13066

CL3R/FPLR/CMR/CMG - MultiConductor Shielded Gray PVC Jacket

300V, 75°C, Multi-Conductor, Shielded, Stranded Copper CL3R/FPLR/CMR/CMG



CONSTRUCTION:

1. **Conductor:** Stranded bare copper per ASTM B8

2. **Insulation:** Polyvinyl Chloride PVC

3. **Shield:** Aluminum foil shielded with 24 AWG drain wire

4. Rip Cord: Rip cord for ease of jacket removal

5. Jacket: Gray Polyvinyl Chloride PVC.

APPLICATIONS AND FEATURES:

Remote Control, Signalling, and Power-Limited circuits per NEC Article 725. 22AWG - 16 AWG also as communication circuits per NEC Article 800. Security, sound and audio, speaker cable, public address, intercom, sound reinforcement, alarm and access control circuits and power-limited controls.

• Flame Test: UI 1666

Cable Type: CL3R, Also, CMR where UL permits (Sizes 16 AWG and smaller)

Voltage: 300 VoltsTemperature: 75°C

SPECIFICATIONS:

ASTM B8 Concentric-Lay-Stranded Copper Conductors

• UL 13 Power-Limited Circuit Cables

• UL 444 Communications Cables (90°C, 300V)

SAMPLE PRINT LEGEND:

XX AWG XX/C E57497 c{UL}US CMR/CL3R/FPLR -- CMG FT4 MADE IN USA ROHS-2 COMPLIANT -- {MM/DD/YY} {HH:MM} {SEQUENTIAL FOOTAGE MARKS} SEQ FEET





Copyright © 2024 Southwire Company, LLC. All Rights Reserved





SPEC 13066 Stock #: R20084-1

Table 1 – Physical and Electrical Data

| Stock Number | Cond. Size | Cond. Number | Cond. Strands | Diameter Over Cond. | Insul. Thickness | Jacket Thickness | Approx. OD | Copper Weight | Approx. Weight | DC Resistance @ 25°C | AC Resistance @ 75°C | Inductive Rectance |
|-----------------|---------------|-----------------|------------------|------------------------|---------------------|---------------------|---------------|------------------|-------------------|----------------------------|----------------------------|-----------------------|
| | AWG | No. | strands | inch | mil | mil | inch | lb / 1000ft | lb /1000ft | Ω /1000ft | Ω /1000ft | Ω/1000ft |
| 22 AWG | | | | | | | | | | | | |
| R20084-1 | 22 | 15 | 7 | 0.022 | 5 | 15 | 0.232 | 33 | 47 | 16.723 | 20.15 | 0.030 |

All dimensions are nominal and subject to normal manufacturing tolerances







[♦] Cable marked with this symbol is a standard stock item