

**SF-2 SEW-2 200°C 600V**

Flexible Silicone Rubber Glass Braid Fixture Wire, Temp Rating 200°C. FT1



Image not to scale. See Table 1 for dimensions.

**CONSTRUCTION:**

1. **Conductor:** Stranded tinned, annealed copper per ASTM B33
2. **Insulation:** Silicone Rubber
3. **Jacket:** Fiberglass braid jacket is applied over the insulation, then treated with a high temperature lacquer finish

**APPLICATIONS AND FEATURES:**

Used for internal wiring of appliances, electrical equipment, and lighting fixtures, as well as hazardous location motors. Excellent electrical properties, flexible, good chemical resistance, contains no chlorine or other halogens, and fungus resistant. Colors available upon request. Rated FT1

**SPECIFICATIONS:**

- ASTM B33 Standard Specification for Tin-Coated Soft or Annealed Copper Wire
- UL AWM Appliance wire approvals as listed in Table 1
- CSA Approved as shown in Table 1
- FT1 Flame Test (1,706 BTU/Hr nominal - Vertical Wire Flame Test)
- RoHS-3 Complies with European Directive 2015/863

Southwire Company, LLC | One Southwire Drive, Carrollton, GA 30119 | [www.southwire.com](http://www.southwire.com)

Copyright © 2024 Southwire Company, LLC. All Rights Reserved

**Southwire****CABLETECH  
SUPPORT™**

Services

UPDATED: Dec. 11, 2023, 9:29 p.m. UTC REVISION: 1.000.000

**Table 1 – Weights and Measurements**

| Stock Number | Cond. Size | Cond. Strands | Insul. Thickness | Braid | Approx. OD | Approx. Weight | Temp. Rating | Standard (UL or other) |
|--------------|------------|---------------|------------------|-------|------------|----------------|--------------|------------------------|
|              | AWG/Kcmil  | strand        | mil              | mil   | inch       | lb/1000ft      | °C           | Style/Type             |
| C0186A       | 18         | 7/.0152       | 30               | 5     | 0.120      | 12.5           | 200          | 3071/SF-2/SEW-2        |
| C0166A       | 16         | 7/.0192       | 30               | 5     | 0.130      | 16             | 200          | 3071/SF-2/SEW-2        |
| C0146A       | 14         | 7/.0242       | 30               | 5     | 0.145      | 22             | 200          | 3071/SF-2/SEW-2        |
| C0126A       | 12         | 19/.0179      | 30               | 5     | 0.165      | 32             | 200          | 3074                   |
| C0106A       | 10         | 19/.0234      | 45               | 5     | 0.220      | 54             | 200          | 3075                   |
| C0086A       | 8          | 54/.0179      | 60               | 7     | 0.295      | 90             | 200          | 3231                   |
| C0066A       | 6          | 84/.0179      | 60               | 7     | 0.325      | 125            | 200          | 3231                   |

All dimensions are nominal and subject to normal manufacturing tolerances

◊ Cable marked with this symbol is a standard stock item

Dimensions and weights for other cable configurations are available upon request.

**Table 2 – Weights and Measurements (Metric)**

| Stock Number | Cond. Size | Cond. Strands | Insul. Thickness | Braid | Approx. OD | Approx. Weight | Temp. Rating | Standard (UL or other) |
|--------------|------------|---------------|------------------|-------|------------|----------------|--------------|------------------------|
|              | AWG/Kcmil  | strand        | mm               | mm    | mm         | kg/km          | °C           | Style/Type             |
| C0186A       | 18         | 7/.0152       | 0.76             | 0.13  | 3.05       | 19             | 200          | 3071/SF-2/SEW-2        |
| C0166A       | 16         | 7/.0192       | 0.76             | 0.13  | 3.30       | 24             | 200          | 3071/SF-2/SEW-2        |
| C0146A       | 14         | 7/.0242       | 0.76             | 0.13  | 3.68       | 33             | 200          | 3071/SF-2/SEW-2        |
| C0126A       | 12         | 19/.0179      | 0.76             | 0.13  | 4.19       | 48             | 200          | 3074                   |
| C0106A       | 10         | 19/.0234      | 1.14             | 0.13  | 5.59       | 80             | 200          | 3075                   |
| C0086A       | 8          | 54/.0179      | 1.52             | 0.18  | 7.49       | 134            | 200          | 3231                   |
| C0066A       | 6          | 84/.0179      | 1.52             | 0.18  | 8.25       | 186            | 200          | 3231                   |

