

HVTECK AL 1/C 175NLEPR TS PVC AIA PVC 15kV 100% CSA

Single Conductor, 175 Mils No Lead Ethylene Propylene Rubber (NL-EPR), 100% Insulation Level, Tape Shield, Polyvinyl Chloride (PVC) Inner Jacket, Aluminum Interlocked Armour (AIA), Polyvinyl Chloride (PVC) Jacket




Image not to scale. See Table 1 for dimensions.

CONSTRUCTION:

1. **Conductor:** Class B compact stranded 8000 Series aluminum per ASTM B800 and ASTM B836
2. **Conductor Shield:** Semi-conducting cross-linked copolymer; A conductor separator is used for cable size larger than or equal to 500 Kcmil
3. **Insulation:** 175 Mils No Lead Ethylene Propylene Rubber (NL-EPR) 100% insulation level
4. **Insulation Shield:** Strippable semi-conducting cross-linked copolymer
5. **Copper Tape Shield:** Helically wrapped 5 mil copper tape with 25% overlap
6. **Inner Jacket:** PVC inner jacket
7. **Armour:** Aluminum Interlocked Armour (AIA)
8. **Overall Jacket:** Red Polyvinyl Chloride (PVC) Jacket

APPLICATIONS AND FEATURES:

Southwire's 15kV HVTECK is a CSA armoured cable for industrial and commercial medium voltage applications. Rated FT4, -40°C, Hazardous Locations (HL). These cables are capable of operating continuously at the conductor temperature not in excess of 105°C for normal operation, 140°C for emergency overload, and 250°C for short circuit conditions. Rated for 1000 lbs /FT maximum sidewall pressure. These cables feature sunlight and moisture resistance, exceptional corona resistance, resistance to most chemical soils and acids and are flame retardant.

SPECIFICATIONS:

- ASTM B801 Concentric-Lay-Stranded Conductors of 8000 Series Aluminum Alloy
- ASTM B836 Compact Rounded Stranded Aluminum Conductors
- CSA C22.2 No. 174 Cables in Hazardous Locations
- CSA C22.2 No. 2556 & No. 0.3 Wire and Cable Test Methods
- CSA C68.10 Shielded Power Cables for Commercial and Industrial Applications - 5 to 46 KV
- CSA C68.3 Shielded & Concentric Neutral Power Cable - 5 to 46 kV
- CSA LTGG [-40°C] - as per C68.10 - for Cold Bend and Impact rating
- CSA HL - for Hazardous Locations rating
- CSA SUN RES - for Sunlight Resistant rating
- ICEA S-93-639 (NEMA WC 74) 5-46 KV Shielded Power Cable
- ICEA T-29-520 Flame Test (210,000 BTU/Hr)
- IEEE 383 Flame Test (70,000 btu)
- IEEE 1202 FT4 Flame Test (70,000) BTU/hr Vertical Tray Test (1/0 and Larger)



- FT1 Flame Test (1,706 BTU/Hr nominal - Vertical Wire Flame Test)
- AEIC CS-8 Specification for extruded dielectric shielded power cables rated for 5 through 46KV

SAMPLE PRINT LEGEND:

(CSA) SOUTHWIRE (NESC) #P# 1/C [#AWG or #kcmil] CPT AL 175 NLEPR AIA 15kV 100% INS LEVEL 25% TS SUN RES 105°C FT4 HL (-40°C) LTGG RoHS YEAR [SEQUENTIAL METER MARKS]

Table 1 – Weights and Measurements

Cond. Size	Strand	Diameter Over Conductor	Diameter Over Insulation	Insul. Thickness	Diameter Over Insulation Shield	Inner Jacket Thickness	Dia. Over Armour	Overall Jacket Thickness	Approx. OD	Approx. Weight
AWG/ Kcmil	No.	inch	inch	mil	inch	mil	inch	mil	inch	lb/1000ft
2	7	0.268	0.656	175	0.716	80	1.118	50	1.218	691
1	19	0.298	0.686	175	0.746	80	1.148	50	1.248	732
1/0	19	0.336	0.724	175	0.784	80	1.186	50	1.286	787
2/0	19	0.376	0.764	175	0.824	80	1.336	50	1.436	858
3/0	19	0.422	0.810	175	0.870	80	1.382	50	1.482	930
4/0	19	0.474	0.862	175	0.922	80	1.434	50	1.534	1016
250	37	0.520	0.916	175	0.976	80	1.488	50	1.588	1103
350	37	0.615	1.011	175	1.071	80	1.583	60	1.703	1312
500	37	0.735	1.131	175	1.191	80	1.727	60	1.847	1596
750	61	0.908	1.314	175	1.374	80	1.910	60	2.030	2099
1000	61	1.060	1.466	175	1.526	110	2.122	60	2.242	2605

All dimensions are nominal and subject to normal manufacturing tolerances

◊ Cable marked with this symbol is a standard stock item

* Strand count meets minimum number per ASTM



Table 2 – Electrical and Engineering Data

Cond. Size	Min Bending Radius	Max Pull Tension	DC Resistance @ 25°C	AC Resistance @ 90°C	Capacitive Reactance @ 60Hz	Inductive Reactance @ 60Hz	Zero Sequence Impedance*	Positive Sequence Impedance*	Phase Short Circuit Current @ 60Hz	Allowable Ampacity In Air 90°C	Allowable Ampacity Directly Buried 90°C
AWG/Kcmil	inch	lb	Ω/1000ft	Ω/1000ft	MΩ/1000ft	Ω/1000ft	Ω/1000ft	Ω/1000ft	Amp	Amp	Amp
2	8.5	398	0.267	0.336	0.046	0.057	0.697 + j0.466	0.337 + j0.056	2218	169	176
1	8.7	502	0.211	0.266	0.043	0.055	0.629 + j0.449	0.267 + j0.053	2311	194	198
1/0	9.0	633	0.168	0.211	0.040	0.053	0.574 + j0.431	0.212 + j0.051	2429	222	223
2/0	10.0	798	0.133	0.167	0.036	0.053	0.529 + j0.412	0.168 + j0.051	2552	255	250
3/0	10.3	1006	0.105	0.133	0.033	0.051	0.494 + j0.392	0.134 + j0.049	2695	290	278
4/0	10.7	1269	0.084	0.105	0.031	0.049	0.465 + j0.371	0.106 + j0.047	2856	329	309
250	11.1	1500	0.071	0.090	0.029	0.047	0.447 + j0.351	0.091 + j0.046	3024	370	347
350	11.9	2100	0.050	0.065	0.025	0.045	0.417 + j0.319	0.066 + j0.043	3318	446	402
500	12.9	3000	0.035	0.046	0.022	0.043	0.388 + j0.283	0.047 + j0.041	3689	533	451
750	14.2	4500	0.024	0.033	0.019	0.040	0.359 + j0.239	0.034 + j0.039	4257	631	500
1000	15.6	6000	0.018	0.026	0.016	0.039	0.338 + j0.21	0.027 + j0.038	4728	707	539

* Inductive impedance is based on non-ferrous conduit with one diameter spacing.

Table 3 – Weights and Measurements (Metric)

Cond. Size	Strand	Diameter Over Conductor	Diameter Over Insulation	Insul. Thickness	Diameter Over Insulation Shield	Inner Jacket Thickness	Dia. Over Armour	Overall Jacket Thickness	Approx. OD	Approx. Weight
AWG/Kcmil	No.	mm	mm	mm	mm	mm	mm	mm	mm	kg/km
2	7	6.81	16.66	4.44	18.19	2.03	28.40	1.27	30.94	1028
1	19	7.57	17.42	4.44	18.95	2.03	29.16	1.27	31.70	1089
1/0	19	8.53	18.39	4.44	19.91	2.03	30.12	1.27	32.66	1171
2/0	19	9.55	19.41	4.44	20.93	2.03	33.93	1.27	36.47	1277
3/0	19	10.72	20.57	4.44	22.10	2.03	35.10	1.27	37.64	1384
4/0	19	12.04	21.89	4.44	23.42	2.03	36.42	1.27	38.96	1512
250	37	13.21	23.27	4.44	24.79	2.03	37.80	1.27	40.34	1641
350	37	15.62	25.68	4.44	27.20	2.03	40.21	1.52	43.26	1952
500	37	18.67	28.73	4.44	30.25	2.03	43.87	1.52	46.91	2375
750	61	23.06	33.38	4.44	34.90	2.03	48.51	1.52	51.56	3124
1000	61	26.92	37.24	4.44	38.76	2.79	53.90	1.52	56.95	3877

All dimensions are nominal and subject to normal manufacturing tolerances

◇ Cable marked with this symbol is a standard stock item

* Strand count meets minimum number per ASTM



Table 4 – Electrical and Engineering Data (Metric)

Cond. Size	Min Bending Radius	Max Pull Tension	DC Resistance @ 25°C	AC Resistance @ 90°C	Capacitive Reactance @ 60Hz	Inductive Reactance @ 60Hz	Zero Sequence Impedance*	Positive Sequence Impedance*	Phase Short Circuit Current @ 60Hz	Allowable Ampacity In Air 90°C	Allowable Ampacity Directly Buried 90°C
AWG/Kcmil	mm	newton	Ω/km	Ω/km	MΩ/km	Ω/km	Ω/1000ft	Ω/1000ft	Amp	Amp	Amp
2	215.90	1771	0.8760	1.10	0.0140	0.1870	0.697 + j0.466	0.337 + j0.056	2218	169	176
1	220.98	2234	0.6923	0.87	0.0131	0.1804	0.629 + j0.449	0.267 + j0.053	2311	194	198
1/0	228.60	2817	0.5512	0.69	0.0122	0.1739	0.574 + j0.431	0.212 + j0.051	2429	222	223
2/0	254.00	3551	0.4364	0.55	0.0110	0.1739	0.529 + j0.412	0.168 + j0.051	2552	255	250
3/0	261.62	4477	0.3445	0.44	0.0101	0.1673	0.494 + j0.392	0.134 + j0.049	2695	290	278
4/0	271.78	5647	0.2756	0.34	0.0094	0.1608	0.465 + j0.371	0.106 + j0.047	2856	329	309
250	281.94	6675	0.2329	0.30	0.0088	0.1542	0.447 + j0.351	0.091 + j0.046	3024	370	347
350	302.26	9345	0.1640	0.21	0.0076	0.1476	0.417 + j0.319	0.066 + j0.043	3318	446	402
500	327.66	13350	0.1148	0.15	0.0067	0.1411	0.388 + j0.283	0.047 + j0.041	3689	533	451
750	360.68	20025	0.0787	0.11	0.0058	0.1312	0.359 + j0.239	0.034 + j0.039	4257	631	500
1000	396.24	26700	0.0591	0.09	0.0049	0.1280	0.338 + j0.21	0.027 + j0.038	4728	707	539

* Inductive impedance is based on non-ferrous conduit with one diameter spacing.

