

Broadband Coax - RG8, RG62, RG174, RG213, RG214, RG223

Southwire®**Quad Shield****Southwire®****Dual Shield**

4

3

2

1

Image not to scale. See Table 1 for dimensions.

CONSTRUCTION:

- Conductor:** Bare copper or copper clad steel
- Insulation:** Polyethylene
- Shield:** Copper braid shielded
- Jacket:** Polyvinyl Chloride PVC.

APPLICATIONS AND FEATURES:

CATV Applications for distributing television signals, using "F" connectors, ALUMINUM BRAID CCTV Applications for surveillance; Connecting security cameras, DVR or monitor using "BNC" connectors, COPPER BRAID

Table 1 – Physical and Electrical Data

Stock Number	Cable Type	Rating	Cond. Size	Cond. Number	Cond. Type	Cond. Strands	Insul. Thickness	Jacket Thickness	Approx. OD	Approx. Weight	Shield Type
			AWG	No.		strands	mil	mil	inch	lb /1000ft	
RG174											
991069	RG174	AWM Style 1354, UL 1	26	1	CCS	7	20	10	0.100	8	Tinned Cu Braid

All dimensions are nominal and subject to normal manufacturing tolerances

◊ Cable marked with this symbol is a standard stock item