



CU 600V PVC-Nylon Insulation PVC Jacket THHN/THWN-2. CT Rated - Sunlight Resistant - For Direct Burial - Silicone Free

Type TC-ER Control Cable 600 Volt Copper Conductors, Polyvinyl Chloride (PVC) with nylon layer Insulation THHN or TFFN/TFN Polyvinyl Chloride (PVC) Jacket, Control Cable Conductor Identification Method 1 Table 2. CT Rated - Sunlight Resistant - For Direct Burial - Silicone Free - VW-1 Rated.



Image not to scale. See Table 1 for dimensions.

CONSTRUCTION:

1. **Conductor:** 7 strands class B compressed bare copper per ASTM B3 and ASTM B8 for 14, 12, and 10 AWG cables. Class K bare copper per ASTM B3 and B174 for 16 AWG (26 strands) and 18 AWG (16 strands) cables
2. **Insulation:** Polyvinyl Chloride (PVC) with nylon layer. Type TFFN/TFN for 18 and 16 AWG cable. Type THHN or THWN-2 for 14, 12, 10 AWG cables. Types THHN or THWN-2 are VW-1 Rated
3. **Filler:** Polypropylene filler on cables with 5 or less conductors
4. **Binder:** Polyester flat thread binder tape applied for cables with more than 5 conductors
5. **Overall Jacket:** Polyvinyl Chloride (PVC) Jacket

APPLICATIONS AND FEATURES:

Southwire's 600 Volt Type TC-ER control cables are suited for use in wet and dry areas, conduits, ducts, troughs, trays, direct burial, aerial supported by a messenger, and where superior electrical properties are desired. These cables are capable of operating continuously at the conductor temperature not in excess of 75°C in wet locations and 90°C in dry locations, 105°C for emergency overload, and 150°C for short circuit conditions. For uses in Class I, II, and III, Division 2 hazardous locations per NEC Article 501 and 502. Constructions with 3 or more conductors are listed for exposed runs (TC-ER) per NEC 336.10. Sunlight Resistant - For Direct Burial - Silicone Free - VW-1 Rated.

SPECIFICATIONS:

- ASTM B3 Soft or Annealed Copper Wire
- ASTM B8 Concentric-Lay-Stranded Copper Conductors
- UL 66 Fixture Wire
- UL 83 Thermoplastic Insulated Wires and Cables
- UL 1277 Electrical Power and Control Tray Cables
- UL 1685 Vertical-Tray Fire Propagation and Smoke Release Test
- ICEA S-58-679 Control Cable Conductor Identification Method 1 Table 2
- ICEA S-73-532 Standard for Control, Thermocouple Extension and Instrumentation Cables
- ICEA S-95-658 (NEMA WC70) Power Cables Rated 2000 Volts or Less for the Distribution of Electrical Energy
- IEEE 1202 FT4 Flame Test (70,000) BTU/hr Vertical Tray Test





SAMPLE PRINT LEGEND:

{SQFTG} SOUTHWIRE® {UL} XX AWG (X.XX{mm²}) CU XX CDRS TYPE TC-ER THHN OR THWN CDRS 90°C JACKET
SUNLIGHT RESISTANT DIRECT BURIAL 600 VOLTS {NOM}-ANCE





Table 1 – Physical and Electrical Data

Stock Number	Cond. Size	Cond. Number	Cond. Strands	Insul. Thickness	Jacket Thickness	Approx. OD	Copper Weight	Approx. Weight	DC Resistance @ 25°C	AC Resistance @ 75°C	Inductive Reactance	Min Bending Radius	Allowable Ampacity 75°C	Allowable Ampacity 90°C	Jacket Color
	AWG	No.	strands	mil	mil	inch	lb / 1000ft	lb / 1000ft	Ω /1000ft	Ω /1000ft	Ω/1000ft	inch	Amp	Amp	
18 AWG															
577879	18	2	7	20	45	0.174	10	15	6.669	8.035	0.036	0.7	-	14	Black
652188	18	3	7	20	45	0.280	15	45	6.669	8.035	0.036	1.1	-	14	Black
577878	18	4	7	20	45	0.304	20	54	6.669	8.035	0.036	1.2	-	11	Black
652191	18	5	7	20	45	0.336	25	66	6.669	8.035	0.036	1.3	-	11	Black
652194	18	6	7	20	45	0.358	30	74	6.669	8.035	0.036	1.4	-	11	Black
652197	18	8	7	20	45	0.385	40	93	6.669	8.035	0.036	1.5	-	9	Black
652200	18	10	7	20	45	0.438	50	140	6.669	8.035	0.036	1.8	-	7	Black
652203	18	12	7	20	45	0.454	60	155	6.669	8.035	0.036	1.8	-	7	Black
652215	18	16	7	20	45	0.508	80	165	6.669	8.035	0.036	2.0	-	7	Black
652209	18	19	7	20	45	0.560	95	239	6.669	8.035	0.036	2.2	-	7	Black
652212	18	24	7	20	60	0.654	121	319	6.669	8.035	0.036	2.6	-	6	Black
16 AWG															
604843◇	16	2	26	20	45	0.292	16	44	4.181	5.037	0.033	1.2	-	18	Black
604850◇	16	3	26	20	45	0.308	24	58	4.181	5.037	0.033	1.2	-	18	Black
604868◇	16	4	26	20	45	0.333	32	70	4.181	5.037	0.033	1.3	-	14	Black
604876◇	16	5	26	20	45	0.362	40	81	4.181	5.037	0.033	1.4	-	14	Black
TBA	16	6	7	20	45	0.380	56	101	4.181	5.037	0.033	1.5	-	14	Black
679257	16	6	26	20	45	0.393	47	97	4.181	5.037	0.033	1.6	-	14	Black
604892◇	16	7	26	20	45	0.393	55	107	4.181	5.037	0.033	1.6	-	12	Black
TBA	16	8	7	20	45	0.410	72	124	4.181	5.037	0.033	1.6	-	12	Black
604918◇	16	9	26	20	45	0.454	72	135	4.181	5.037	0.033	1.8	-	12	Black
TBA	16	10	7	20	45	0.476	88	151	4.181	5.037	0.033	1.9	-	9	Black
604942◇	16	12	26	20	45	0.510	95	174	4.181	5.037	0.033	2.0	-	9	Black
604975	16	15	26	20	45	0.595	120	226	4.181	5.037	0.033	2.4	-	9	Black
605014◇	16	19	26	20	60	0.625	152	274	4.181	5.037	0.033	2.5	-	9	Black
TBA	16	20	7	20	60	0.632	168	286	4.181	5.037	0.033	2.5	-	9	Black
605071	16	25	26	20	60	0.700	201	350	4.181	5.037	0.033	2.8	-	8	Black
605121	16	30	26	20	60	0.767	242	412	4.181	5.037	0.033	3.1	-	8	Black
605196◇	16	37	26	20	60	0.867	297	529	4.181	5.037	0.033	3.5	-	7	Black
14 AWG															
408484◇	14	2	7	20	45	0.305	25	56	2.631	3.170	0.058	1.2	20	25	Black
408518◇	14	3	7	20	45	0.322	38	74	2.631	3.170	0.058	1.3	20	25	Black
408542◇	14	4	7	20	45	0.351	51	94	2.631	3.170	0.058	1.4	16	20	Black
408575◇	14	5	7	20	45	0.380	64	109	2.631	3.170	0.058	1.5	16	20	Black
608836	14	6	7	20	45	0.416	76	130	2.631	3.170	0.058	1.7	16	20	Black
TBA	14	8	7	20	45	0.456	115	176	2.631	3.170	0.058	1.8	14	17	Black
408740◇	14	9	7	20	45	0.490	115	189	2.631	3.170	0.058	2.0	14	17	Black
605477	14	10	7	20	45	0.556	128	222	2.631	3.170	0.058	2.2	10	12	Black
408807◇	14	12	7	20	45	0.573	153	256	2.631	3.170	0.058	2.3	10	12	Black





Stock Number	Cond. Size	Cond. Number	Cond. Strands	Insul. Thickness	Jacket Thickness	Approx. OD	Copper Weight	Approx. Weight	DC Resistance @ 25°C	AC Resistance @ 75°C	Inductive Reactance	Min Bending Radius	Allowable Ampacity 75°C	Allowable Ampacity 90°C	Jacket Color
	AWG	No.	strands	mil	mil	inch	lb / 1000ft	lb / 1000ft	Ω /1000ft	Ω /1000ft	Ω/1000ft	inch	Amp	Amp	
412874	14	15	7	20	60	0.632	192	312	2.631	3.170	0.058	2.5	10	12	Black
412908	14	19	7	20	60	0.664	243	381	2.631	3.170	0.058	2.7	10	12	Black
608729	14	20	7	20	60	0.697	256	401	2.631	3.170	0.058	2.8	10	12	Black
552133	14	25	7	20	60	0.802	320	507	2.631	3.170	0.058	3.2	9	11	Black
557553	14	30	7	20	60	0.875	384	620	2.631	3.170	0.058	3.5	9	11	Black
552190	14	37	7	20	80	0.949	475	759	2.631	3.170	0.058	3.8	8	10	Black
12 AWG															
408468	12	2	7	20	45	0.348	40	77	1.662	2.002	0.054	1.4	25	30	Black
408526	12	3	7	20	45	0.369	61	108	1.662	2.002	0.054	1.5	25	30	Black
408559	12	4	7	20	45	0.401	81	149	1.662	2.002	0.054	1.6	20	24	Black
408583	12	5	7	20	45	0.438	101	183	1.662	2.002	0.054	1.8	20	24	Black
408641	12	7	7	20	45	0.477	142	237	1.662	2.002	0.054	1.9	17	21	Black
608737	12	6	7	20	45	0.481	122	189	1.662	2.002	0.054	1.9	20	24	Black
TBA	12	8	7	20	60	0.546	182	268	1.662	2.002	0.054	2.2	17	21	Black
408757	12	9	7	20	60	0.580	183	332	1.662	2.002	0.054	2.3	17	21	Black
TBA	12	10	7	20	60	0.634	223	326	1.662	2.002	0.054	2.5	12	15	Black
408815	12	12	7	20	60	0.657	244	425	1.662	2.002	0.054	2.6	12	15	Black
412882	12	15	7	20	60	0.734	305	454	1.662	2.002	0.054	2.9	12	15	Black
622420	12	16	7	20	60	0.738	325	478	1.662	2.002	0.054	3.0	12	15	Black
412916	12	19	7	20	60	0.772	388	562	1.662	2.002	0.054	3.1	12	15	Black
TBA	12	20	7	20	60	0.802	426	585	1.662	2.002	0.054	3.2	12	15	Black
552166	12	25	7	20	80	0.943	509	761	1.662	2.002	0.054	3.8	11	13	Black
TBA	12	30	7	20	80	0.982	630	879	1.662	2.002	0.054	3.9	11	13	Black
552224	12	37	7	20	80	1.064	755	1084	1.662	2.002	0.054	5.3	10	12	Black
10 AWG															
408492	10	2	7	25	45	0.420	64	115	1.040	1.253	0.050	1.7	35	40	Black
408534	10	3	7	25	45	0.446	97	159	1.040	1.253	0.050	1.8	35	40	Black
408567	10	4	7	25	45	0.505	129	207	1.040	1.253	0.050	2.0	28	32	Black
408591	10	5	7	25	45	0.565	161	258	1.040	1.253	0.050	2.3	28	32	Black
TBA	10	6	7	25	60	0.611	226	325	1.040	1.253	0.050	2.4	28	32	Black
408658	10	7	7	25	60	0.615	226	381	1.040	1.253	0.050	2.5	24	28	Black
TBA	10	8	7	25	60	0.662	290	406	1.040	1.253	0.050	2.6	24	28	Black
408765	10	9	7	25	60	0.715	291	501	1.040	1.253	0.050	2.9	24	28	Black
TBA	10	10	7	25	60	0.774	355	496	1.040	1.253	0.050	3.1	17	20	Black
408823	10	12	7	25	60	0.806	388	652	1.040	1.253	0.050	3.2	17	20	Black
601666	10	19	7	25	80	0.993	613	903	1.040	1.253	0.050	4.0	17	20	Black
TBA	10	20	7	25	80	1.028	678	941	1.040	1.253	0.050	5.1	17	20	Black
TBA	10	25	7	25	80	1.140	840	1149	1.040	1.253	0.050	5.7	15	18	Black
TBA	10	30	7	25	80	1.207	1002	1349	1.040	1.253	0.050	6.0	15	18	Black
TBA	10	37	7	25	80	1.303	1228	1631	1.040	1.253	0.050	6.5	14	16	Black

All dimensions are nominal and subject to normal manufacturing tolerances





◇ Cable marked with this symbol is a standard stock item

* Ampacities based upon 2023 NEC Table 310.16 and do not take into account the overcurrent protection limitations in NEC 240.4(D) of 15 Amps for 14 AWG CU, 20 Amps for 12 AWG CU, and 30 Amps for 10 AWG CU (independent of the conductor temperature rating and stranding if size is present in table). Also, see NEC sections 310.15 and 110.14(C) for additional requirements.

* Ampacities have been adjusted for more than Three Current-Carrying Conductors.

TBA stock codes are estimations only and actual product may vary. Please wait until a stock code is assigned to purchase connectors and/or fittings.

