# PowerGlide Quadruplex 600 Volt Underground Service Entrance

Aluminum Conductor. Cross-linked Polyethylene (XLP) Insulation. HI-SCORE available upon request. Easy to Pull or Push.




Image not to scale. See Table 1 for dimensions.

## CONSTRUCTION:

1. **Conductor:** Conductors are stranded, compressed 1350-H16/H26 (3/4 Hard) aluminum
2. **Insulation:** Cross Linked Polyethylene (XLPE). LLDPE or HDPE based polymer
3. **Neutral:** Cross Linked Polyethylene (XLPE) with three Yellow Extruded Stripes (YES)
4. **PowerGlide:** Engineered spiral-wrapped glide wire that reduces installation friction and maintains bundle integrity

**For information about our Cable-Rejuvenation Services please visit us at:** Cable-Rejuvenation Services
**You can email us at:** Cable-Rejuvenation Services

## APPLICATIONS AND FEATURES:

Conductors are stranded, compressed 1350-H16/H26 (3/4 Hard) aluminum, insulated with cross-linked polyethylene. Neutrals are identified by three yellow extruded stripes "YES". Cables with "YES" neutrals have sequential footage markers. Conductors are durably surface printed for identification. Two-phase conductors and one neutral conductor are cabled together to produce the triplex cable configuration. Twisted conductors are bound with an engineered spiral-wrapped glide wire that reduces installation friction and maintains bundle integrity. These cables are capable of operating continuously at the conductor temperature not in excess of 90°C for normal operation in wet and dry locations, 130°C for emergency overload, and 250°C for short circuit conditions

## SPECIFICATIONS:

- ASTM B231 Standard Specification for Concentric-Lay-Stranded Aluminum 1350 Conductors
- ASTM B609 Standard Specification for Aluminum 1350 Round Wire, Annealed and Intermediate Tempers, for Electrical Purposes
- ASTM 786 19 Wire Combination Unilay-Stranded Aluminum Conductors
- ASTM B901 Standard Specification for Compressed Round Stranded Aluminum Conductors Using Single Input Wire Construction. *(The number of strands for both phase and neutral may differ)*
- UL 854 Service Entrance Cable
- ICEA S-81-570 Standard for 600 Volt Rated Cables of Ruggedized Design for Direct Burial Installations as Single Conductors or Assemblies of Single Conductors
- ICEA S-105-692 Standard For 600 Volt Single Layer Thermoset Insulated Utility Underground Distribution Cables

We've got it MADE IN AMERICA



Copyright © 2026 Southwire Company, LLC. All Rights Reserved

UPDATED: Dec. 31, 2024, 11:09 p.m.UTC REVISION: 1.000.001

## Table 1 – Weights and Measurements

| Code Word | Phase Cond. Size | Phase Strand | Dia. Over Phase Conductor | Phase Insul. Thickness | Dia. Over Phase Insulation | Neutral Cond. Size | Neutral Strand | Neutral Insul. Thickness | Approx. OD | Approx. Weight |
|---|---|---|---|---|---|---|---|---|---|---|
| | AWG/ Kcmil | No. | inch | mil | inch | AWG/Kcmil | No. | mil | inch | lb/1000ft |
| NOTRE DAME | 1/0 | 19 | 0.362 | 80 | 0.522 | 2 | 6 | 60 | 1.263 | 513 |
| PURDUE | 1/0 | 19 | 0.362 | 80 | 0.522 | 1/0 | 7 | 80 | 1.263 | 550 |
| SYRACUSE | 2/0 | 19 | 0.405 | 80 | 0.565 | 1 | 7 | 80 | 1.367 | 635 |
| LAFAYETTE | 2/0 | 19 | 0.405 | 80 | 0.565 | 2/0 | 11 | 80 | 1.367 | 682 |
| SWARTHMORE | 3/0 | 19 | 0.456 | 80 | 0.616 | 1/0 | 7 | 80 | 1.491 | 791 |
| DAVIDSON | 3/0 | 19 | 0.456 | 80 | 0.616 | 3/0 | 15 | 80 | 1.491 | 849 |
| WAKE FOREST | 4/0 | 19 | 0.512 | 80 | 0.672 | 2/0 | 11 | 80 | 1.626 | 985 |
| EARLHAM | 4/0 | 19 | 0.512 | 80 | 0.672 | 4/0 | 17 | 80 | 1.626 | 1058 |
| SLIPPERY ROCK | 350 | 37 | 0.661 | 95 | 0.851 | 4/0 | 17 | 80 | 2.059 | 1613 |
| MOREHOUSE | 500 | 37 | 0.789 | 95 | 0.979 | 300 | 18 | 95 | 2.369 | 2266 |
| WESTMINSTER | 750 | 61 | 0.968 | 110 | 1.188 | 350 | 24 | 95 | 2.875 | 3362 |
| WABASH | 750 | 61 | 0.968 | 110 | 1.188 | 4/0 | 17 | 80 | 2.875 | 3232 |

All dimensions are nominal and subject to normal manufacturing tolerances

Notes:

1. The actual number of strands may differ for single input wire per ASTM B901

TBA stock codes are estimations only and actual product may vary. Please wait until a stock code is assigned to purchase connectors and/or fittings.

## Table 2 – Electrical and Engineering Data

| Code Word | Phase Cond. Size | Min Bending Radius | Max Pull Tension | DC Resistance @ 25°C | AC Resistance @ 75°C | Inductive Reactance @ 60Hz | Allowable Ampacity in Duct or Buried 75/90°C |
|---|---|---|---|---|---|---|---|
| | AWG/Kcmil | inch | lb | Ω/1000ft | Ω/1000ft | Ω/1000ft | Amp |
| NOTRE DAME | 1/0 | 6.3 | 2534 | 0.167 | 0.208 | 0.044 | 120/135 |
| PURDUE | 1/0 | 6.3 | 2534 | 0.167 | 0.208 | 0.044 | 120/135 |
| SYRACUSE | 2/0 | 6.8 | 3194 | 0.133 | 0.166 | 0.043 | 135/150 |
| LAFAYETTE | 2/0 | 6.8 | 3194 | 0.133 | 0.166 | 0.043 | 135/150 |
| SWARTHMORE | 3/0 | 7.5 | 4027 | 0.105 | 0.131 | 0.042 | 155/175 |
| DAVIDSON | 3/0 | 7.5 | 4027 | 0.105 | 0.131 | 0.042 | 155/175 |
| WAKE FOREST | 4/0 | 8.1 | 5078 | 0.084 | 0.105 | 0.041 | 180/205 |
| EARLHAM | 4/0 | 8.1 | 5078 | 0.084 | 0.105 | 0.041 | 180/205 |
| SLIPPERY ROCK | 350 | 12.4 | 8400 | 0.051 | 0.064 | 0.04 | 250/280 |
| MOREHOUSE | 500 | 14.2 | 12000 | 0.036 | 0.045 | 0.039 | 310/350 |
| WESTMINSTER | 750 | 17.2 | 18000 | 0.023 | 0.03 | 0.038 | 385/435 |
| WABASH | 750 | 17.2 | 18000 | 0.023 | 0.03 | 0.038 | 385/435 |

Notes:

1. Inductive reactance assumes cables are cradled in conduit, and the neutral is carrying no current.
2. Triple parallel inductive reactance calculation assumes the phase conductors are adjacent to one another.
3. Conductors assumed to be reverse lay stranded, compressed construction.
4. Phase spacing assumes cables are touching.
5. Resistances shown are for the Phase conductors only.
6. Ampacity based on 90°C conductor temperature, 20°C ambient, RHO 90, 100% load factor.

We've got it
MADE IN AMERICA



Copyright © 2026 Southwire Company, LLC. All Rights Reserved

UPDATED: Dec. 31, 2024, 11:09 p.m.UTC REVISION: 1.000.001