



Duraclad® Type MC 277/480V Colors

14 AWG through 10 AWG Copper THHN/THWN Insulated Singles. Green Copper THHN Insulated Grounding Conductor. UL Listed. 600 Volts. Rated VW-1. Lightweight Steel Interlocked Armor. Also available in Blue Steel Armor.



Image not to scale. See Table 1 for dimensions.

CONSTRUCTION:

1. **Conductor:** Solid copper per ASTM B3 or 19-strand class C compressed copper and ASTM B3 and B8
2. **Insulation:** Polyvinyl Chloride with Nylon Sheath Type THHN/THWN
3. **Ground:** Green Polyvinyl Chloride with Nylon Sheath Type THHN/THWN insulated ground conductor
4. **Binder:** Mylar tape with print legend wrapped around assembly
5. **Aarmor:** Light weight galvanized steel interlocked armor

APPLICATIONS AND FEATURES:

Southwire Duraclad® Type MC Cable is suitable for use as follows:

- Branch and service power distribution in commercial, industrial, institutional, and multi-residential buildings
- Fished or embedded in plaster
- Concealed or exposed installations
- Environmental air-handling spaces per NEC 300.22 (C)
- Places of Assembly per NEC 518.4 and theaters per NEC 520.5
- Installation in cable tray and approved raceways
- Under raised floors for information technology equipment conductors and cables per NEC Article 645
- Class I Div. 2, Class II Div. 2, & Class III Div. 1 Hazardous Locations
- Binder tape with print legend wrapped around assembly
- Type THHN/THWN rated 90°C dry
- Unjacketed Type MC cables are rated for dry, indoor locations only per NEC 330.10(A)(10)
- Anti-Short bushing not required

Southwire Duraclad® Type MC Cable meets or exceeds the following requirements:

- UL Online Product Guide Info - Metal-Clad Cable (PJAZ) (www.ul.com)
- Federal Specification A-A59544 (formerly J-C-30B)
- NFPA 70 (National Electrical Code), Article 330
- Listed for use in UL 1, 2 and 3 Hour Through Penetration Firestop Systems

SPECIFICATIONS:

- ASTM B3 Soft or Annealed Copper Wire
- ASTM B8 Concentric-Lay-Stranded Copper Conductors
- UL 83 Thermoplastic Insulated Wires and Cables





- UL 1569 Metal-Clad Cables
- UL 1479 Standard for Safety Fire Tests of Penetration Firestops
- UL 1685 FT4 Vertical-Tray Fire Propagation and Smoke Release Test
- IEEE 1202 FT4 Flame Test (70,000) BTU/hr Vertical Tray Test
- RoHS-2 (European Directive 2011/65/EU)
- Buy American: Compliant with Buy American Requirements, found in 49 U.S.C. § 5323(j); specify “Made in the USA Only!” when ordering to ensure your project receives American made products.
- VW-1 (Vertical-Wire) Flame Test

SAMPLE PRINT LEGEND:

SOUTHWIRE E96627 {UL} TYPE MC XX AWG THHN OR THWN CDRS FOR USE IN CABLE TRAYS 600 VOLTS




Table 1 – Weights and Measurements

Stock Number	Cond. Size	Conductor Number	Color	Diameter Over Conductor	Conductor Stranding	Insulation Thickness	Ground Size	Diameter Over Armor	Copper Weight	Overall Weight
	AWG/ Kcmil			inch		mils	No. x AWG	inch	lbs/ 1000ft	lbs/ 1000ft
12 AWG Solid										
553111	12	2	BN,GY,GN	0.08	Solid	20	1x12	0.484	59	206
556205	12	2	PE,GY,GN	0.08	Solid	20	1x12	0.484	59	206
553272	12	3	PE,BN,GY,GN	0.08	Solid	20	1x12	0.515	79	239
553241	12	3	GY,BN,OE,GN	0.08	Solid	20	1x12	0.515	79	239
678479	12	4	OE,YW,GY/OE,GY/ YW,GN	0.08	Solid	20	1x12	0.549	99	277
678480	12	4	BN,YW,GY/BN,GY/ YW,GN	0.08	Solid	20	1x12	0.549	99	277
678478	12	4	BN,OE,GY/BN,GY/ OE,GN	0.08	Solid	20	1x12	0.549	99	277
553242◇	12	2	OE,GY,GN	0.080	Solid	20	1x12	0.483	59	151
551774◇	12	2	BN,GY,GN	0.080	Solid	20	1x12	0.487	59	152
553243◇	12	2	YW,GY,GN	0.080	Solid	20	1x12	0.483	59	151
553251◇	12	3	BN,YW,GY,GN	0.080	Solid	20	1x12	0.514	79	181
553244◇	12	4	BN,OE,YW,GY,GN	0.080	Solid	20	1x12	0.549	99	213
12 AWG 19 Strands										
586374	12	2	YW,GY,GN	0.088	19	20	1x12	0.505	60	215
586372	12	2	OE,GY,GN	0.088	19	20	1x12	0.505	60	215
559749	12	2	BN,GY,GN	0.088	19	20	1x12	0.505	60	215
10 AWG Solid										
551782◇	10	2	YW,GY,GN	0.101	Solid	25	1x10	0.550	92	204
553250◇	10	2	BN,GY,GN	0.101	Solid	25	1x10	0.550	92	204
551783◇	10	2	OE,GY,GN	0.101	Solid	25	1x10	0.550	92	204
551787◇	10	3	BN,YW,GY,GN	0.101	Solid	25	1x10	0.589	123	251
553252◇	10	3	BN,OE,GY,GN	0.101	Solid	25	1x10	0.589	123	251
587525	10	4	BN,YW,GY/BN,GY/ YW,GN	0.101	Solid	25	1x10	0.634	154	374
553245◇	10	4	BN,OE,YW,GY,GN	0.101	Solid	25	1x10	0.633	154	296
649653	10	6	BN,OE,YW,GY/BN,GY/ OE,GY/YW,GN	0.101	Solid	25	1x10	0.679	216	381
644587	1	3	BN,OE,YW,GN	0.322	19	60	1x6	1.253	864	1400

All dimensions are nominal and subject to normal manufacturing tolerances

◇ Cable marked with this symbol is a standard stock item

Note: Conductor number = number of phase conductors plus neutrals (if any). Does not include green ground.

TBA stock codes are estimations only and actual product may vary. Please wait until a stock code is assigned to purchase connectors and/or fittings.





Table 2 – Electrical and Engineering Data

Cond. Size	Conductor Number	Min. Bend Radius	DC Resistance at 25°C	AC Resistance at 75°C	Inductive Reactance @ 60Hz	Allowable Ampacity Raceway 75°C	Allowable Ampacity Raceway 90°C
AWG/Kcmil		Inches	Ω/1000ft	Ω/1000ft	Ω/1000ft	Amp	Amp
12 AWG Solid							
12	2	3.4	1.662	2.002	0.054	25	30
12	2	3.4	1.662	2.002	0.054	25	30
12	3	3.6	1.662	2.002	0.054	25	24
12	3	3.6	1.662	2.002	0.054	25	24
12	4	3.8	1.662	2.002	0.054	20	24
12	4	3.8	1.662	2.002	0.054	20	24
12	4	3.8	1.662	2.002	0.054	20	24
12	2	3.4	1.662	2.002	0.054	25	30
12	2	3.4	1.662	2.002	0.054	25	30
12	2	3.4	1.662	2.002	0.054	25	30
12	3	3.6	1.662	2.002	0.054	25	30
12	4	3.8	1.662	2.002	0.054	20	24
12 AWG 19 Strands							
12	2	3.5	1.662	2.002	0.054	25	30
12	2	3.5	1.662	2.002	0.054	25	30
12	2	3.5	1.662	2.002	0.054	25	30
10 AWG Solid							
10	2	3.9	1.040	1.253	0.050	35	40
10	2	3.9	1.040	1.253	0.050	35	40
10	2	3.9	1.040	1.253	0.050	35	40
10	3	4.1	1.040	1.253	0.050	35	40
10	3	4.1	1.040	1.253	0.050	35	40
10	4	4.4	1.04	1.253	0.05	28	32
10	4	4.4	1.040	1.253	0.050	28	32
10	6	4.8	1.04	1.253	0.05	28	28
1	3	8.8	0.128	0.154	0.046	130	145

* Ampacities based upon 2023 NEC Table 310.16 and do not take into account the overcurrent protection limitations in NEC 240.4(D) of 15 Amps for 14 AWG CU, 20 Amps for 12 AWG CU, and 30 Amps for 10 AWG CU (independent of the conductor temperature rating and stranding if size is present in table). Also, see NEC sections 310.15 and 110.14(C) for additional requirements.

* Ampacities have been adjusted for more than Three Current-Carrying Conductors.

