



MC-AP™ Type MC All Purpose THHN/THWN Circuit Size Copper Conductor 120/208V Colors

Copper THHN Insulated Conductors. Full-Sized Aluminum Equipment Grounding/Bonding Conductor. UL Listed 600 Volt. Rated VW1. Lightweight Aluminum Interlocked Armor is Part of Equipment Bonding/Grounding Path.




Image not to scale. See Table 1 for dimensions.

CONSTRUCTION:

1. **Conductor:** Solid or 19 strands class C compressed copper per ASTM B3 and ASTM B8
2. **Insulation:** All phases are insulated with Polyvinyl Chloride with Nylon Sheath Type THHN/THWN
3. **Binder:** Mylar tape
4. **Ground:** Full-sized bare 8000 series aluminum grounding/bonding conductor. Armor and bare aluminum conductor form the equipment ground path.
5. **Armor:** Aluminum Interlocked Armor

APPLICATIONS AND FEATURES:

Southwire MC-AP All Purpose Type MC Cable is suitable for use as follows:

- Branch, feeder and service power distribution in commercial, industrial, institutional, and multi- residential buildings.
- Fished or embedded in plaster.
- Concealed or exposed installations.
- Environmental air-handling spaces per NEC 300.22 (C).
- Places of Assembly per NEC 518.4 and theaters per NEC 520.5.
- Installation in cable tray and approved raceways.
- Under raised floors for information technology equipment conductors and cables per NEC 645.5(D) & 645.5(D)(2)
- Class I Div. 2, Class II Div 2, & Class III Div. 1 Hazardous Locations.
- Binder tape with print legend wrapped around assembly.
- Type THHN/THWN rated 90°C Dry.

Southwire Armorlite® Type MC Cable - meets or exceeds the following requirements:

- UL Online Product Guide Info - Metal-Clad Cable (PJAZ) (www.ul.com)
- Federal Specification A-A59544 (formerly J-C-30B)
- NFPA 70 (National Electrical Code), Article 330
- Listed for use in UL 1, 2 and 3 Hour Through Penetration Firestop Systems

SPECIFICATIONS:

- ASTM B3 Soft or Annealed Copper Wire
- ASTM B8 Concentric-Lay-Stranded Copper Conductors
- UL 83 Thermoplastic Insulated Wires and Cables





- UL 1569 Metal-Clad Cables
- UL 1479 Standard for Safety Fire Tests of Penetration Firestops
- UL 1685 FT4 Vertical-Tray Fire Propagation and Smoke Release Test
- IEEE 1202 FT4 Flame Test (70,000) BTU/hr Vertical Tray Test
- RoHS-2 (European Directive 2011/65/EU)
- Buy American: Compliant with Buy American Requirements, found in 49 U.S.C. § 5323(j); specify “Made in the USA Only!” when ordering to ensure your project receives American made products.

SAMPLE PRINT LEGEND:

E96627 {UL} TYPE MC XX AWG THHN OR THWN CDRS FOR USE IN CABLE TRAYS 600 VOLTS -- ARMOR IS EQUIPMENT GROUNDING PATH COMPONENT




Table 1 – Weights and Measurements

Stock Number	Cond. Size	Conductor Number	Color	Diameter Over Conductor	Conductor Stranding	Insulation Thickness	Diameter Over Armor	Copper Weight	Overall Weight
	AWG/ Kcmil			inch		mils	inch	lbs/1000ft	lbs/1000ft
14 AWG Solid									
5552720	14	2	BK,WE	0.064	Solid	20	0.451	25	70
5552730	14	3	BK,RD,WE	0.064	Solid	20	0.468	37	87
5552740	14	4	BK,RD,BE,WE	0.064	Solid	20	0.495	50	105
12 AWG Solid									
559841	12	2	BK,RD	0.08	Solid	20	0.481	39	91
559686	12	3	RD,WE,BE	0.08	Solid	20	0.512	59	118
559684	12	3	BK,WE,BE	0.08	Solid	20	0.506	59	117
567193	12	6	BK,RD,BE,WE/BK,WE/ RD,WE/BE	0.08	Solid	20	0.61	119	199
567246	12	6	BK,BK/WE,RD/WE,RD,WE/ BK,WE	0.08	Solid	20	0.61	119	199
558832	12	8	BK,BK/WE,RD,RD/ WE,BE,BE/WE,WE,WE/BK	0.08	Solid	20	0.648	159	251
5587680	12	2	RD,WE	0.080	Solid	20	0.493	39	92
5587700	12	2	BE,WE	0.080	Solid	20	0.487	39	92
5551030	12	2	BK,WE	0.080	Solid	20	0.487	39	92
5551040	12	3	BK,RD,WE	0.080	Solid	20	0.506	59	117
5551050	12	4	BK,RD,BE,WE	0.080	Solid	20	0.544	79	145
12 AWG 19 Strands									
596058	12	3	RD,PE,WE	0.088	19	20	0.534	60	123
567208	12	4	BK,RD,WE/BK,WE/RD	0.088	19	20	0.568	80	151
10 AWG Solid									
5552750	10	2	BK,WE	0.101	Solid	25	0.555	61	130
559972	10	2	BE,WE	0.101	Solid	25	0.561	61	132
559969	10	2	RD,WE	0.101	Solid	25	0.561	61	132
5552770	10	3	BK,RD,WE	0.101	Solid	25	0.580	92	169
562278	10	4	BK,RD,WE/BK,WE/RD	0.101	Solid	25	0.619	123	210
5552780	10	4	BK,RD,BE,WE	0.101	Solid	25	0.619	123	210
558837	10	6	BK,BK/WE,RD,RD/ WE,WE,WE/BK	0.101	Solid	25	0.709	185	292
567197	10	6	BK,RD,BE,WE/BK,WE/ RD,WE/BE	0.101	Solid	25	0.709	185	292
10 AWG 19 Strands									
555875	10	4	BK,WE,RD,BE	0.113	19	25	0.656	129	225
567218	10	6	BK,RD,BE,WE/BK,WE/ RD,WE/BE	0.113	19	25	0.731	194	325
567267	10	6	BK,RD,BK/WE,RD/WE,WE/ BK,WE	0.113	19	25	0.755	194	310
567030	8	2	BK,WE	0.141	19	35	0.688	102	198
567033	8	3	BK,RD,WE	0.141	19	35	0.722	154	265
12 AWG 19 Strands									





Stock Number	Cond. Size	Conductor Number	Color	Diameter Over Conductor	Conductor Stranding	Insulation Thickness	Diameter Over Armor	Copper Weight	Overall Weight
	AWG/Kcmil			inch		mils	inch	lbs/1000ft	lbs/1000ft
558788◇	12	2	BE,WE	0.090	19	20	0.507	40	95
558786◇	12	2	RD,WE	0.090	19	20	0.507	40	95
556377◇	12	2	BK,WE	0.090	19	20	0.438	40	90
556457◇	12	3	BK,RD,WE	0.090	19	20	0.528	60	122
555874◇	12	4	BK,RD,BE,WE	0.090	19	20	0.562	80	150
10 AWG 19 Strands									
557387◇	10	2	BK,WE	0.117	19	25	0.586	64	139
557390◇	10	3	BK,RD,WE	0.117	19	25	0.613	97	181

All dimensions are nominal and subject to normal manufacturing tolerances

◇ Cable marked with this symbol is a standard stock item

TBA stock codes are estimations only and actual product may vary. Please wait until a stock code is assigned to purchase connectors and/or fittings.





Table 2 – Electrical and Engineering Data

Cond. Size	Conductor Number	Min. Bend Radius	DC Resistance at 25°C	AC Resistance at 75°C	Inductive Reactance @ 60Hz	Allowable Ampacity Raceway 75°C	Allowable Ampacity Raceway 90°C
AWG/Kcmil		Inches	Ω/1000ft	Ω/1000ft	Ω/1000ft	Amp	Amp
14 AWG Solid							
14	2	3.2	2.631	3.170	0.058	20	25
14	3	3.3	2.631	3.170	0.058	20	25
14	4	3.5	2.631	3.170	0.058	16	20
12 AWG Solid							
12	2	3.4	1.662	2.002	0.054	25	30
12	3	3.6	1.662	2.002	0.054	20	24
12	3	3.5	1.662	2.002	0.054	20	24
12	6	4.3	1.662	2.002	0.054	17	21
12	6	4.3	1.662	2.002	0.054	17	21
12	8	4.5	1.662	2.002	0.054	12	15
12	2	3.5	1.662	2.002	0.054	25	30
12	2	3.4	1.662	2.002	0.054	25	30
12	2	3.4	1.662	2.002	0.054	25	30
12	3	3.5	1.662	2.002	0.054	25	30
12	4	3.8	1.662	2.002	0.054	20	24
12 AWG 19 Strands							
12	3	3.7	1.662	2.002	0.054	20	24
12	4	4	1.662	2.002	0.054	20	24
10 AWG Solid							
10	2	3.9	1.040	1.253	0.050	35	40
10	2	3.9	1.04	1.253	0.05	35	40
10	2	3.9	1.04	1.253	0.05	35	40
10	3	4.1	1.040	1.253	0.050	35	40
10	4	4.3	1.04	1.253	0.05	28	32
10	4	4.3	1.040	1.253	0.050	28	32
10	6	5	1.04	1.253	0.05	24	28
10	6	5	1.04	1.253	0.05	24	28
10 AWG 19 Strands							
10	4	4.6	1.04	1.253	0.05	28	32
10	6	5.1	1.04	1.253	0.05	24	28
10	6	5.3	1.04	1.253	0.05	24	28
8	2	4.8	0.653	0.786	0.052	50	55
8	3	5.1	0.653	0.786	0.052	40	44
12 AWG 19 Strands							
12	2	3.5	1.662	2.002	0.054	25	30
12	2	3.5	1.662	2.002	0.054	25	30
12	2	3.1	1.662	2.002	0.054	25	30
12	3	3.7	1.662	2.002	0.054	25	30
12	4	3.9	1.662	2.002	0.054	20	24





Cond. Size	Conductor Number	Min. Bend Radius	DC Resistance at 25°C	AC Resistance at 75°C	Inductive Reactance @ 60Hz	Allowable Ampacity Raceway 75°C	Allowable Ampacity Raceway 90°C
AWG/Kcmil		Inches	Ω/1000ft	Ω/1000ft	Ω/1000ft	Amp	Amp
10 AWG 19 Strands							
10	2	4.1	1.040	1.253	0.050	35	40
10	3	4.3	1.040	1.253	0.050	35	40

* Ampacities based upon 2023 NEC Table 310.16 and do not take into account the overcurrent protection limitations in NEC 240.4(D) of 15 Amps for 14 AWG CU, 20 Amps for 12 AWG CU, and 30 Amps for 10 AWG CU (independent of the conductor temperature rating and stranding if size is present in table). Also, see NEC sections 310.15 and 110.14(C) for additional requirements.

* Ampacities have been adjusted for more than Three Current-Carrying Conductors.

MCAP Savings Calculator

