



## Fire Alarm FPLR Solid Non-Shielded

300V, 75°C, Multi-Conductor, Unshielded, Solid Copper as FPLR. Rated CMR/CL3R/FPLR CMG SUN RES FT4. Minimum Temperature -10°C , Maximum Temperature 75°C



Image not to scale. See Table 1 for dimensions.

### CONSTRUCTION:

1. **Conductor:** Solid bare copper per ASTM B3
2. **Insulation:** Low Smoke Polyvinyl Chloride LS-PVC
3. **Rip Cord:** Rip cord for ease of jacket removal
4. **Jacket:** Low Smoke Polyvinyl Chloride LS-PVC, Color: RED

### APPLICATIONS AND FEATURES:

Fire protective signaling circuits. Also for smoke detectors, voice communications, audio control and initiating circuits. Article 760 of the NEC. Minimum Temperature -10°C , Maximum Temperature 75°C

### SPECIFICATIONS:

- UL 1424 Cables for Power-Limited Fire-Alarm Circuits
- UL1424 Listed FPLR
- NFPA 70 NFPA 101, NFPA 130, and NFPA 502
- UL 13 Power-Limited Circuit Cables
- UL 444 Communications Cables (90°C, 300V)
- RoHS-2 (European Directive 2011/65/EU)

### SAMPLE PRINT LEGEND:

XX AWG X/C E75610 C{UL}US CMR/CL3R/FPLR SUN RES -- CMG FT4 MADE IN USA ROHS-2 COMPLIANT -- {MM/DD/YY}  
{HH:MM} {SEQUENTIAL FOOTAGE MARKS} SEQ FEET





**Table 1 – Physical and Electrical Data**

| Stock Number | Cond. Size | Cond. Number | Cond. Strands | Diameter Over Cond. | Insul. Thickness | Jacket Thickness | Approx. OD | Copper Weight | Approx. Weight | DC Resistance @ 25°C | AC Resistance @ 75°C | Min Bending Radius |
|--------------|------------|--------------|---------------|---------------------|------------------|------------------|------------|---------------|----------------|----------------------|----------------------|--------------------|
|              | AWG        | No.          | strands       | inch                | mil              | mil              | inch       | lb / 1000ft   | lb / 1000ft    | Ω /1000ft            | Ω /1000ft            | inch               |
| 18 AWG       |            |              |               |                     |                  |                  |            |               |                |                      |                      |                    |
| F40021-1     | 18         | 2            | Solid         | 0.040               | 10               | 15               | 0.200      | 10            | 18             | 6.669                | 8.030                | 0.8                |
| F40568-1     | 18         | 4            | Solid         | 0.040               | 10               | 15               | 0.242      | 20            | 33             | 6.669                | 8.030                | 0.9                |
| 16 AWG       |            |              |               |                     |                  |                  |            |               |                |                      |                      |                    |
| F50004-1     | 16         | 2            | Solid         | 0.050               | 10               | 15               | 0.220      | 16            | 26             | 4.181                | 5.030                | 0.8                |
| F50383-1     | 16         | 4            | Solid         | 0.050               | 10               | 15               | 0.266      | 32            | 47             | 4.181                | 5.030                | 1.0                |
| 14 AWG       |            |              |               |                     |                  |                  |            |               |                |                      |                      |                    |
| F60001-1     | 14         | 2            | Solid         | 0.064               | 10               | 15               | 0.248      | 25            | 38             | 2.631                | 3.170                | 0.9                |
| F60355-1     | 14         | 4            | Solid         | 0.064               | 10               | 15               | 0.300      | 51            | 69             | 2.631                | 3.170                | 1.2                |
| 12 AWG       |            |              |               |                     |                  |                  |            |               |                |                      |                      |                    |
| F70004-1     | 12         | 2            | Solid         | 0.080               | 10               | 15               | 0.280      | 40            | 55             | 1.662                | 2.000                | 1.1                |

All dimensions are nominal and subject to normal manufacturing tolerances

◇ Cable marked with this symbol is a standard stock item

