



## CU 600V XLPE Insulation. CT Rated - Sunlight Resistant - Silicone Free

Power Cable 600 Volt Single Conductor Copper, Cross Linked Polyethylene (XLPE) insulation XHHW-2 Polyvinyl Chloride (PVC) Jacket. CT Rated 1/0 and Larger - Sunlight Resistant - Silicone Free



Image not to scale. See Table 1 for dimensions.

### CONSTRUCTION:

1. **Conductor:** Class B compressed stranded bare copper per ASTM B3 and ASTM B8
2. **Insulation:** Cross Linked Polyethylene (XLPE) Type XHHW-2
3. **Overall Jacket:** Polyvinyl Chloride (PVC) Jacket

### APPLICATIONS AND FEATURES:

Southwire's 600 Volt power cables are suited for use in wet and dry areas, conduits, ducts, troughs, trays, aerial supported by a messenger, and where superior electrical properties are desired. These cables are capable of operating continuously at the conductor temperature not in excess of 90°C for normal operation in wet and dry locations, 130°C for emergency overload, and 250°C for short circuit conditions. CT Rated 1/0 and Larger - Sunlight Resistant - Silicone Free. Rated for 1000 lbs./FT maximum sidewall pressure.

### SPECIFICATIONS:

- ASTM B3 Soft or Annealed Copper Wire
- ASTM B8 Concentric-Lay-Stranded Copper Conductors
- UL 44 Thermoset-Insulated Wires and Cables
- UL 1685 Vertical-Tray Fire Propagation and Smoke Release Test (1/0 and Larger)
- ICEA S-95-658 (NEMA WC70) Power Cables Rated 2000 Volts or Less for the Distribution of Electrical Energy
- CT USE Sizes 1/0 AWG and Larger

### SAMPLE PRINT LEGEND:

{SQFTG} SOUTHWIRE {UL} XX AWG CU TYPE XHHW-2/PVC JKT XX MILS XLP XX MILS PVC SUNLIGHT RESISTANT FOR CT USE 600V 90°C





**Table 1 – Weights and Measurements**

| Stock Number | Cond. Size    | Cond. Number | Strand Count   | Diameter Over Conductor | Insul. Thickness | Jacket Thickness | Approx. OD | Copper Weight | Approx. Weight |
|--------------|---------------|--------------|----------------|-------------------------|------------------|------------------|------------|---------------|----------------|
|              | AWG/<br>Kcmil |              | No. of Strands | inch                    | mil              | mil              | inch       | lb/1000ft     | lb/1000ft      |
| 890419       | 1/0           | 1            | 19             | 0.361                   | 55               | 50               | 0.590      | 325           | 431            |
| 890181       | 2/0           | 1            | 19             | 0.405                   | 55               | 50               | 0.634      | 410           | 526            |
| TBA          | 3/0           | 1            | 19             | 0.456                   | 55               | 50               | 0.666      | 518           | 614            |
| 890180       | 4/0           | 1            | 19             | 0.498                   | 55               | 50               | 0.726      | 653           | 790            |
| 890023       | 250           | 1            | 37             | 0.542                   | 65               | 60               | 0.836      | 771           | 970            |
| TBA          | 300           | 1            | 37             | 0.610                   | 65               | 60               | 0.860      | 926           | 997            |
| 890179       | 350           | 1            | 37             | 0.661                   | 65               | 75               | 0.935      | 1080          | 1307           |
| 890022       | 500           | 1            | 37             | 0.789                   | 65               | 75               | 1.060      | 1543          | 1807           |
| TBA          | 600           | 1            | 61             | 0.865                   | 80               | 75               | 1.175      | 1853          | 2111           |
| 890024       | 750           | 1            | 61             | 0.968                   | 80               | 75               | 1.294      | 2315          | 2674           |
| TBA          | 1000          | 1            | 61             | 1.117                   | 80               | 75               | 1.427      | 3088          | 3410           |

All dimensions are nominal and subject to normal manufacturing tolerances

◊ Cable marked with this symbol is a standard stock item

TBA stock codes are estimations only and actual product may vary. Please wait until a stock code is assigned to purchase connectors and/or fittings.

**Table 2 – Electrical and Engineering Data**

| Stock Number | Cond. Size    | Cond. Number | Min Bending Radius | Max Pull Tension | DC Resistance @ 25°C | AC Resistance @ 75°C | Inductive Reactance @ 60Hz | Allowable Ampacity At 75°C | Allowable Ampacity At 90°C |
|--------------|---------------|--------------|--------------------|------------------|----------------------|----------------------|----------------------------|----------------------------|----------------------------|
|              | AWG/<br>Kcmil |              | inch               | lb               | Ω/1000ft             | Ω/1000ft             | Ω/1000ft                   | Amp                        | Amp                        |
| 890419       | 1/0           | 1            | 2.3                | 844              | 0.102                | 0.122                | 0.044                      | 150                        | 170                        |
| 890181       | 2/0           | 1            | 2.5                | 1064             | 0.081                | 0.097                | 0.043                      | 175                        | 195                        |
| TBA          | 3/0           | 1            | 2.7                | 1342             | 0.064                | 0.078                | 0.042                      | 200                        | 225                        |
| 890180       | 4/0           | 1            | 2.9                | 1692             | 0.051                | 0.062                | 0.041                      | 230                        | 260                        |
| 890023       | 250           | 1            | 3.2                | 2000             | 0.043                | 0.053                | 0.041                      | 255                        | 290                        |
| TBA          | 300           | 1            | 3.4                | 2400             | 0.036                | 0.045                | 0.041                      | 285                        | 320                        |
| 890179       | 350           | 1            | 3.7                | 2800             | 0.031                | 0.039                | 0.040                      | 310                        | 350                        |
| 890022       | 500           | 1            | 5.3                | 4000             | 0.022                | 0.029                | 0.039                      | 380                        | 430                        |
| TBA          | 600           | 1            | 5.9                | 4800             | 0.018                | 0.025                | 0.039                      | 420                        | 475                        |
| 890024       | 750           | 1            | 6.5                | 6000             | 0.014                | 0.022                | 0.038                      | 475                        | 535                        |
| TBA          | 1000          | 1            | 7.1                | 8000             | 0.011                | 0.018                | 0.037                      | 545                        | 615                        |

\* Ampacities based upon 2023 NEC Table 310.16 and do not take into account the overcurrent protection limitations in NEC 240.4(D) of 15 Amps for 14 AWG CU, 20 Amps for 12 AWG CU, and 30 Amps for 10 AWG CU (independent of the conductor temperature rating and stranding if size is present in table). Also, see NEC sections 310.15 and 110.14(C) for additional requirements.

\* Inductive Reactance is based on non-ferrous conduit with one diameter spacing center-to-center.

